

## Increased viewing distance LED wall mounted exit signs

Large format maintained or non maintained emergency exit luminaires with a choice of legends and increased viewing distance. SmartScan wireless versions available.

- Extremely long LED lifetime, up to 100,000 hours
- 60 m maximum viewing distance in accordance with BS EN 1838
- Three hour, maintained emergency operation
- Choice of ISO 7010 legends
- Simple to install, full status reporting SmartScan wireless communication versions



IP20

0 LL/CW

SMART-SCAN

### Specification

Mounting	Surface	IP rating	IP20
----------	---------	-----------	------

### Emergency data

Legend type	ISO 7010 arrow down ISO 7010 arrow left ISO 7010 arrow right ISO 7010 arrow up	Maximum viewing distance	60 m
Emergency type	Maintained (wire link may be removed to enable non-maintained operation)	Emergency duration	3 hours
Battery specification	Nickel Metal Hydride (NiMH)		

### Power

LED power	3 W	Circuit power	4 W - 4.5 W
-----------	-----	---------------	-------------


### LED characteristics

Colour temperature	4000 K		
--------------------	--------	--	--

### Compliance

UKCA	Yes	CE	Yes
------	-----	----	-----

## Dimensions



View the  
range



Information is correct as of 20-Dec-2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.