# Jubilee-XL



### LED surface mounted controller luminaires

Surface mounted luminaires with 'Satin-Glo' polycarbonate side controllers providing high angle illuminance. Micro-prism lens (LED) provide main illumination element and cut off. Assists compliance with EN12464-1 / LG7 (<3000 cd/m<sup>2</sup> @ 65°).

Applications: schools, colleges, hospitals and areas with computer

- 'Satin-Glo' polycarbonate controller provides high angle illuminance
- Excellent optical design for EN12464-1 / LG7 (<3000 cd/m<sup>2</sup> @ 65°) compliance
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



Up to 151.9 LL/CW IP40





### **Specification**

Mounting Surface IP rating IP40 1200 mm Nominal size Max presence detection height 8 m 1500 mm

## Lighting

Efficacy

2,635 lm - 7,120 lm Optic Satin-Glo diffuser Lumen output Up to 151.9 LL/CW

## **Emergency data**

**Emergency lumen output** 390 lm - 575 lm Emergency type Maintained **Emergency duration** 3 hours Battery specification Nickel Metal Hydride (NiMH)

#### **Power**

14 W - 43 W 18 W - 50 W LED power Circuit power

### **LED characteristics**

CRI 4000 K 80+ Colour temperature

Rated life (hours) 67 K - L80/B10




## Compliance

UKCA Yes CE Yes

Energy efficiency class This product contains a light source of

energy efficiency class A

## **Dimensions**





Information is correct as of 20-Dec-2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice