

High performance LED pole top luminaires

Stylish IP66 rated pole top amenity luminaire with aluminium cast body and spigot adaptor. UV stabilised polycarbonate cover rated IP66 and IK10. Integral high quality LED driver.

Applications: car parks, amenity areas and hospital estates.

- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Photocell option
- Zero upward light



IP66

IK10

Up to 136.3 LL/CW

LUXGUARD

Specification

| | | | |
|---------------|--------|----------------|---------------------|
| Mounting | Column | IP rating | IP66 |
| Impact rating | IK10 | Windage rating | 0.04 m ² |

Lighting

| | | | |
|----------|-------------------|--------------|----------------------|
| Optic | Clear cover | Lumen output | 5,380 lm - 13,560 lm |
| Efficacy | Up to 136.3 LL/CW | | |

Power

| | | | |
|-----------|--------------|---------------|--------------|
| LED power | 37 W - 101 W | Circuit power | 42 W - 110 W |
|-----------|--------------|---------------|--------------|


LED characteristics

| | | | |
|--------------------|-----------------|--------------------|--------|
| CRI | 70+ | Colour temperature | 4000 K |
| Rated life (hours) | 100 K - L80/B10 | | |

Compliance

| | | | |
|-------------------------|---|----|-----|
| UKCA | Yes | CE | Yes |
| Energy efficiency class | This product contains a light source of energy efficiency class B | | |

Dimensions



View the
range



Information is correct as of 20-Dec-2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.