

Retrofit kit for Dot luminaires

Energy saving, fast installation retrofit solution.

- 100,000 hour LED life expectancy
- Suitable for existing 28 W and 38 W, 452 mm diameter versions
- Significantly improved efficiency; power consumption more than halved compared with 38W 2D
- Easy to install
- Suitable for retrofit into existing standard, emergency and AutoTest Dot luminaire



0 LL/CW

LUXGUARD

Lighting management

Emergency system

AutoTest Emergency
Non-emergency
Standard Emergency

Lighting

Lumen Output (Multiple)

Satin Sparkle 2500 lm / Opal 1865 lm

Efficacy

0 LL/CW

Efficacy (Multiple)

Up to Satin Sparkle 156.3 ll/cw / Opal
116.6 ll/cw

Emergency data

Emergency Lumen Output

Satin Sparkle 460 lm / Opal 340 lm

Emergency type

Maintained

Emergency duration

3 hours

Battery specification

Nickel Metal Hydride (NiMH)

Power

LED power

13 W

Circuit power

16 W

LED characteristics

CRI

80+

Colour temperature

4000 K

Rated life (hours)

100 K - L80/B10

Compliance

UKCA

Yes

CE

Yes

Energy efficiency class

This product contains a light source of
energy efficiency class B

Spares

Product code	Description	Weight
DOT15069	Satin sparkle effect polycarbonate cover	-



View the
range

