

Circular anti-ligature recessed LED downlighters

Circular recessed anti-ligature luminaires. Choice of clear or satin 4 mm thick polycarbonate diffuser secured via strong spun steel ring using tamper-resistant pin Torx screws. SmartScan Radar and maintained emergency versions available.

- Anti-pick sealant can be used to seal the mounting bezel whilst still allowing the luminaire to be removed for maintenance
- Cover secured using tamper-resistant T20 pin Torx screws
- Supplied with remote gear unit fitted with 2 m supply lead
- SmartScan Radar versions with sensor discretely hidden behind the cover



IP65 (IP20 above ceiling)

IK10

Up to 106.5 LL/CW

SMARTSCAN

LUXGUARD

Specification

Mounting	Recessed	IP rating	IP65 (IP20 above ceiling)
Impact rating	IK10	Max presence detection height	4 m

Lighting

Optic	Clear cover Satin cover	Lumen output	835 lm - 1,940 lm
Efficacy	Up to 106.5 LL/CW		

Emergency data

Emergency lumen output	260 lm - 330 lm	Emergency type	Maintained
Emergency duration	3 hours	Battery specification	Nickel Metal Hydride (NiMH)

Power

LED power	8 W - 16 W	Circuit power	10 W - 19 W
-----------	------------	---------------	-------------

LED characteristics


CRI	80+	Colour temperature	4000 K
Rated life (hours)	63 K - L80/B10		

Compliance

SmartScan wireless standards compliance

Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724

Dimensions



View the range



Information is correct as of 23-Nov-2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.