Juno A



LED pole top amenity luminaires

Stylish IP66 rated pole top amenity luminaire with aluminium cast body and spigot adaptor. UV stabilised clear polycarbonate cover rated IP66 and IK10. Integral high quality LED driver.

Applications: car parks, amenity areas and hospital estates.

- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Photocell option



IP66

IK10

Up to 120 LL/CW

\ r	101	- 14:	C 3	•.	on
- OL	, – ,		La	L	OH.

Mounting Column IP rating IP66

Impact rating IK10 Windage rating 0.14 m²

Lighting

Optic Clear cover Lumen output 4,320 lm - 6,825 lm

Efficacy Up to 120 LL/CW

Power

LED power 31 W - 52 W Circuit power 36 W - 61 W

LED characteristics

CRI 70+ Colour temperature 4000 K

Rated life (hours) 100 K - L90/B10

Juno A




Compliance

UKCA Yes CE Yes

Energy efficiency class This product contains a light source

of energy efficiency class D

Dimensions







Click or scan here

View Juno A variants using our online filtering tool



 $Information\ is\ correct\ as\ of\ 21-Jan-2025,\ however\ must\ not\ be\ interpreted\ as\ a\ guarantee\ of\ individual\ product\ performance\ and/or\ characteristics.\ We\ reserve\ the\ right\ to\ alter\ specifications$

Juno A

and designs without prior notice.

